

Delock WLAN 802.11 b/g/n Antenna RP-SMA 7 dBi Omnidirectional Joint With Magnetic Stand

Description

This Wireless LAN antenna can be connected to your device with RP-SMA interface, in order to send and receive signals. Due to the three tilt stages of the flexible antenna and the magnetic stand you can place the antenna individually.



Item no. 88410

EAN: 4043619884100

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Technical details

- Connectors: 1 x RP-SMA plug
- Frequency range: 2.4 - 2.5 GHz
- Antenna gain: 7 dBi
- Impedance: 50 Ohm
- Cable type: RG-174
- Cable attenuation: 0.9 dB @ 800 MHz per meter
- Cable colour: black
- Cable length: ca. 1 m
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: black
- Length:
 - ca. 297.6 mm (with tilt joint)
 - ca. 260.0 mm (without tilt joint)
- Diameter:
 - ca. 16.0 mm (top)
 - ca. 60.0 mm (magnetic base)

Package content

- WLAN antenna

Images



General

Mounting type:	magnetic
----------------	----------

Interface

Connector:	1 x RP-SMA plug
------------	-----------------

Technical characteristics

Frequency range:	2400 - 2500 MHz
Antenna gain:	7 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	vertical linear
VSWR:	2.0

Physical characteristics

Antenna type:	omnidirectional
Diameter magnetic base:	60.0 mm
Housing material:	ABS
Cable type:	RG-174
Cable attenuation:	0.9 dB @ 800 MHz per meter
Cable colour:	black
Cable length:	1 m
Diameter:	16.0 mm
Length with tilt joint:	297.6 mm
Length without tilt joint:	260.0 mm
Colour:	black

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de